

**SIDHE PETROCHEMICALS PRIVATE LIMITED**

R.S. No. 445,446/1,446/2,448,449, Village Bhimasar,
Taluka Anjar, District Kutch, 370240, Gujarat.

CERTIFICATE OF ANALYSISREPORT NO. **SPPL/BM/PB/0001**

DATE

PRODUCT NAME **SH 100 DA**
QUANTITY
INVOICE NO.
CUSTOMER NAME.
BATCH NO.
PACKING IN
VEHICLE NO.

ANY SOL D 100

S.NO	CHARACTERISTICS	UNIT	TEST METHOD	SPECIFICATION	TYPICAL VALUES
1	APPEARANCE	-	VISUAL	BRIGHT & CLEAR	BRIGHT & CLEAR
2	COLOR, Saybolt		ASTM D 156	30 Max	0.803
3	DENSITY @ 29.5 °C	g/ml	ASTD D1298	0.825 Max	30
4	FLASH POINT	deg C	ASTM D 93	Min 100	116
5	IBP	deg C	ASTM D 86	235 Min.	248
6	FBP	deg C	ASTM D 86	275 Max	266
7	ANILINE POINT	deg C	ASTM D 611	80+/- 2	80
8	KIN.VISCOSITY @ 40 °C	mm ² /s	ASTM D 445	2.00 - 2.80	2.54
9	POUR POINT	deg C	ASTM D 97	-20 Max	-24
10	WATER CONTENT	ppm	ASTM D 1744	100 max	32.11

DISCLAIMER

(1) The information given here is considered to be correct is offered for your consideration investigation & verification .
(2) No warranties are expressed or implied since the use of products are beyond our control.

Tested By**Approved by****Q C Chemist****Manager QC**

FM/QC/002,0.00;0723