

**SIDHE PETROCHEMICALS PRIVATE LIMITED**

R.S. No. 445,446/1,446/2,448,449, Village Bhimasar,  
Taluka Anjar, District Kutch, 370240, Gujarat.

**CERTIFICATE OF ANALYSIS**REPORT NO. **SPPL/BM/PB/000**

DATE

PRODUCT NAME **KL 30 PF**

S.NO	CHARACTERISTICS	UNIT	TEST METHOD	SPECIFICATION	TYPICAL VALUES
1	APPEARANCE@ 20°C	-	VISUAL	BRIGHT & CLEAR	BRIGHT & CLEAR
2	DENSITY @ 29.5 °C	g/ml	ASTD D1298	0.750 Max	0.719
3	COLOR, Saybolt		ASTM D 156	30 Max	30
4	FLASH POINT	deg C	ASTM D 93	Min 25	32
5	IBP	deg C	ASTM D 86	140 Min.	146
6	DRY POINT	deg C	ASTM D 86	170 max	166
7	KIN.VISCOSITY @ 40 °C	mm <sup>2</sup> /s	ASTM D 445	1.0 Max	0.865
8	AROMATIC CONTENT	PPM	BY UV	<300	60
9	ACIDITY	mgKOH/G	ASTMD 974	0.005 Max	NIL

**DISCLAIMER**

(1) The information given here is considered to be correct is offered for your consideration investigation & verification .  
(2) No warranties are expressed or implied since the use of products are beyond our control.

Tested By

QC Chemist

Approved by

Manager QC

FM/QC/002,0.00;0723