

SIDHE PETROCHEMICALS PRIVATE LIMITED																																																											
R.S. No. 445,446/1,446/2,448,449, Village Bhimasar, Village Bhimasar, Taluka Anjar, District Kutch, 370240, Gujarat.																																																											
CERTIFICATE OF ANALYSIS																																																											
REPORT NO.	SPPL/BM/PB/0056	DATE																																																									
PRODUCT NAME	SH 40 PLUS																																																										
<table border="1"> <thead> <tr> <th>S.NO</th> <th>CHARACTERISTICS</th> <th>UNIT</th> <th>TEST METHOD</th> <th>SPECIFICATION</th> <th>TYPICAL VALUES</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>APPEARANCE@ 20°C</td> <td>-</td> <td>VISUAL</td> <td>BRIGHT & CLEAR</td> <td>BRIGHT & CLEAR</td> </tr> <tr> <td>2</td> <td>DENSITY @ 29.5 °C</td> <td>g/ml</td> <td>ASTD D1298</td> <td>0.750 Max</td> <td>0.730</td> </tr> <tr> <td>3</td> <td>COLOR, Saybolt</td> <td>-</td> <td>ASTM D 156</td> <td>30 Max</td> <td>30</td> </tr> <tr> <td>4</td> <td>FLASH POINT</td> <td>deg C</td> <td>ASTM D 93</td> <td>Min 40</td> <td>43</td> </tr> <tr> <td>5</td> <td>IBP</td> <td>deg C</td> <td>ASTM D 86</td> <td>150 Min.</td> <td>156</td> </tr> <tr> <td>6</td> <td>FBP</td> <td>deg C</td> <td>ASTM D 86</td> <td>220, Max</td> <td>198</td> </tr> <tr> <td>7</td> <td>KIN.VISCOSITY @ 40 °C</td> <td>mm²/s</td> <td>ASTM D 445</td> <td>1.5 Max</td> <td>0.88</td> </tr> <tr> <td>8</td> <td>POUR POINT</td> <td>deg C</td> <td>ASTM D 97</td> <td>-42 Max</td> <td>-42</td> </tr> </tbody> </table>						S.NO	CHARACTERISTICS	UNIT	TEST METHOD	SPECIFICATION	TYPICAL VALUES	1	APPEARANCE@ 20°C	-	VISUAL	BRIGHT & CLEAR	BRIGHT & CLEAR	2	DENSITY @ 29.5 °C	g/ml	ASTD D1298	0.750 Max	0.730	3	COLOR, Saybolt	-	ASTM D 156	30 Max	30	4	FLASH POINT	deg C	ASTM D 93	Min 40	43	5	IBP	deg C	ASTM D 86	150 Min.	156	6	FBP	deg C	ASTM D 86	220, Max	198	7	KIN.VISCOSITY @ 40 °C	mm ² /s	ASTM D 445	1.5 Max	0.88	8	POUR POINT	deg C	ASTM D 97	-42 Max	-42
S.NO	CHARACTERISTICS	UNIT	TEST METHOD	SPECIFICATION	TYPICAL VALUES																																																						
1	APPEARANCE@ 20°C	-	VISUAL	BRIGHT & CLEAR	BRIGHT & CLEAR																																																						
2	DENSITY @ 29.5 °C	g/ml	ASTD D1298	0.750 Max	0.730																																																						
3	COLOR, Saybolt	-	ASTM D 156	30 Max	30																																																						
4	FLASH POINT	deg C	ASTM D 93	Min 40	43																																																						
5	IBP	deg C	ASTM D 86	150 Min.	156																																																						
6	FBP	deg C	ASTM D 86	220, Max	198																																																						
7	KIN.VISCOSITY @ 40 °C	mm ² /s	ASTM D 445	1.5 Max	0.88																																																						
8	POUR POINT	deg C	ASTM D 97	-42 Max	-42																																																						
DISCLAIMER (1) The information given here is considered to be correct is offered for your consideration investigation & verification . (2) No warranties are expressed or implied since the use of products are beyond our control.																																																											
Tested By					Approved by																																																						
Q.C. Chemist					Manager QC FM/QC/002,0.00;0723																																																						

SIDHE PETROCHEMICALS PRIVATE LIMITED																																																											
R.S. No. 445,446/1,446/2,448,449, Village Bhimasar, Village Bhimasar, Taluka Anjar, District Kutch, 370240, Gujarat.																																																											
CERTIFICATE OF ANALYSIS																																																											
REPORT NO.	SPPL/BM/PB/0057	DATE	28.04.2025																																																								
PRODUCT NAME	SH 40 PLUS																																																										
INVOICE NO.	SPPL/2425/00443																																																										
CUSTOMER NAME	M/S. KONNARK POLYCHEM LLP																																																										
LOT / BATCH NO.	SPAF04250128																																																										
QUANTITY	26820 KGS																																																										
PACKING IN	TANKER																																																										
VEHICLE NO.	GJ12 BX 8408																																																										
<table border="1"> <thead> <tr> <th>S.NO</th> <th>CHARACTERISTICS</th> <th>UNIT</th> <th>TEST METHOD</th> <th>SPECIFICATION</th> <th>TYPICAL VALUES</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>APPEARANCE@ 20°C</td> <td>-</td> <td>VISUAL</td> <td>BRIGHT & CLEAR</td> <td>BRIGHT & CLEAR</td> </tr> <tr> <td>2</td> <td>DENSITY @ 29.5 °C</td> <td>g/ml</td> <td>ASTD D1298</td> <td>0.750 Max</td> <td>0.730</td> </tr> <tr> <td>3</td> <td>COLOR, Saybolt</td> <td>-</td> <td>ASTM D 156</td> <td>30 Max</td> <td>30</td> </tr> <tr> <td>4</td> <td>FLASH POINT</td> <td>deg C</td> <td>ASTM D 93</td> <td>Min 40</td> <td>43</td> </tr> <tr> <td>5</td> <td>IBP</td> <td>deg C</td> <td>ASTM D 86</td> <td>150 Min.</td> <td>156</td> </tr> <tr> <td>6</td> <td>FBP</td> <td>deg C</td> <td>ASTM D 86</td> <td>220, Max</td> <td>198</td> </tr> <tr> <td>7</td> <td>KIN.VISCOSITY @ 40 °C</td> <td>mm²/s</td> <td>ASTM D 445</td> <td>1.5 Max</td> <td>0.88</td> </tr> <tr> <td>8</td> <td>POUR POINT</td> <td>deg C</td> <td>ASTM D 97</td> <td>-42 Max</td> <td>-42</td> </tr> </tbody> </table>						S.NO	CHARACTERISTICS	UNIT	TEST METHOD	SPECIFICATION	TYPICAL VALUES	1	APPEARANCE@ 20°C	-	VISUAL	BRIGHT & CLEAR	BRIGHT & CLEAR	2	DENSITY @ 29.5 °C	g/ml	ASTD D1298	0.750 Max	0.730	3	COLOR, Saybolt	-	ASTM D 156	30 Max	30	4	FLASH POINT	deg C	ASTM D 93	Min 40	43	5	IBP	deg C	ASTM D 86	150 Min.	156	6	FBP	deg C	ASTM D 86	220, Max	198	7	KIN.VISCOSITY @ 40 °C	mm ² /s	ASTM D 445	1.5 Max	0.88	8	POUR POINT	deg C	ASTM D 97	-42 Max	-42
S.NO	CHARACTERISTICS	UNIT	TEST METHOD	SPECIFICATION	TYPICAL VALUES																																																						
1	APPEARANCE@ 20°C	-	VISUAL	BRIGHT & CLEAR	BRIGHT & CLEAR																																																						
2	DENSITY @ 29.5 °C	g/ml	ASTD D1298	0.750 Max	0.730																																																						
3	COLOR, Saybolt	-	ASTM D 156	30 Max	30																																																						
4	FLASH POINT	deg C	ASTM D 93	Min 40	43																																																						
5	IBP	deg C	ASTM D 86	150 Min.	156																																																						
6	FBP	deg C	ASTM D 86	220, Max	198																																																						
7	KIN.VISCOSITY @ 40 °C	mm ² /s	ASTM D 445	1.5 Max	0.88																																																						
8	POUR POINT	deg C	ASTM D 97	-42 Max	-42																																																						

DISCLAIMER

(1) The information given here is considered to be correct is offered for your consideration investigation & verification .
(2) No warranties are expressed or implied since the use of products are beyoud our control.

Tested By**Q.C Chemist****Approved by****Manager QC**

FM/QC/002,0.00;0723