

 SIDHE PETROCHEMICALS PRIVATE LIMITED R.S. No. 445,446/1,446/2,448,449, Village Bhimasar, Taluka Anjar, District Kutch, 370240, Gujarat.					
CERTIFICATE OF ANALYSIS					
REPORT NO.	SPPL/BM/PB/0147	DATE			
PRODUCT NAME	SH 55 PF				
REF NO.					
CUSTOMER NAME					
QUANTITY					
PLACE					
S.NO	CHARACTERISTICS	UNI T	TEST METHOD	SPECIFICATION	TYPICAL VALUES
1	APPEARANCE@ 20°C	-	VISUAL	BRIGHT & CLEAR	BRIGHT & CLEAR
2	DENSITY @ 29.5 °C	g/ml	ASTD	0.750 Max	0.735
3	COLOR, Saybolt		ASTM D	30 Max	30
4	FLASH POINT	deg	ASTM D 93	Min 40	58
5	IBP	deg	ASTM D 86	150 Min.	178
6	FBP	deg	ASTM D 86	220, Min.	254
7	KIN.VISCOSITY @ 40 °C	mm ²	ASTM D	1.5 Max	1.21
8	POUR POINT	deg	ASTM D 97	≤42	-42
DISCLAIMER					
(1) The information given here is considered to be correct is offered for your consideration investigation & verification .					
(2) No warranties are expressed or implied since the use of products are beyond our control.					
Tested By	Approved by				
QC Chemist	Manager QC FM/QC/002,0.00,0723				

 SIDHE PETROCHEMICALS PRIVATE LIMITED R.S. No. 445,446/1,446/2,448,449, Village Bhimasar, Taluka Anjar, District Kutch, 370240, Gujarat.					
CERTIFICATE OF ANALYSIS					
REPORT NO.	SPPL/BM/PB/0162	DATE	07.06.2025		
PRODUCT NAME	SH 55 PF				
REF NO.	0162/2025				
CUSTOMER NAME	M/S. APAR INDUSTRIES LTD				
QUANTITY	02 X 01 LTRS				
PLACE	MUMBAI				
S.NO	CHARACTERISTICS	UNI T	TEST METHOD	SPECIFICATION	TYPICAL VALUES
1	APPEARANCE@ 20°C	-	VISUAL	BRIGHT & CLEAR	BRIGHT & CLEAR
2	DENSITY @ 29.5 °C	g/ml	ASTD	0.750 Max	0.735
3	COLOR, Saybolt		ASTM D	30 Max	30
4	FLASH POINT	deg	ASTM D 93	Min 40	58
5	IBP	deg	ASTM D 86	150 Min.	178
6	FBP	deg	ASTM D 86	220, Min.	254
7	KIN.VISCOSITY @ 40 °C	mm ²	ASTM D	1.5 Max	1.21
8	POUR POINT	deg	ASTM D 97	≤42	-42
DISCLAIMER					
(1) The information given here is considered to be correct is offered for your consideration investigation & verification .					
(2) No warranties are expressed or implied since the use of products are beyond our control.					
Tested By	Approved by				
QC Chemist	Manager QC FM/QC/002,0.00,0723				

 SIDHE PETROCHEMICALS PRIVATE LIMITED R.S. No. 445,446/1,446/2,448,449, Village Bhimasar, Taluka Anjar, District Kutch, 370240, Gujarat.					
CERTIFICATE OF ANALYSIS					
REPORT NO.	SPPL/BM/PB/0181	DATE	16.06.2025		
PRODUCT NAME	SH 55 PF				
REF NO.	0181/2025				
CUSTOMER NAME	M/S. ANAND ENGINEERING				
QUANTITY	01 X 05 LTR				
PLACE	MAHARASHTRA				
S.NO	CHARACTERISTICS	UNI T	TEST METHOD	SPECIFICATION	TYPICAL VALUES
1	APPEARANCE@ 20°C	-	VISUAL	BRIGHT & CLEAR	BRIGHT & CLEAR
2	DENSITY @ 29.5 °C	g/ml	ASTD	0.750 Max	0.735
3	COLOR, Saybolt		ASTM D	30 Max	30
4	FLASH POINT	deg	ASTM D 93	Min 40	58
5	IBP	deg	ASTM D 86	150 Min.	178
6	FBP	deg	ASTM D 86	220, Min.	254
7	KIN.VISCOSITY @ 40 °C	mm ²	ASTM D	1.5 Max	1.21
8	POUR POINT	deg	ASTM D 97	≤42	-42
DISCLAIMER					
(1) The information given here is considered to be correct is offered for your consideration investigation & verification .					
(2) No warranties are expressed or implied since the use of products are beyond our control.					
Tested By	Approved by				
QC Chemist	Manager QC FM/QC/002,0.00,0723				