



SIDHE PETROCHEMICALS PRIVATE LIMITED

R.S. No. 445,446/1,446/2,448,449, Village Bhimasar,
Taluka Anjar, District Kutch, 370240, Gujarat.

CERTIFICATE OF ANALYSIS

REPORT NO. SPPL/BM/PB/000

Date

PRODUCT NAME KL 80 DA

| S.NO | CHARACTERISTICS | UNIT | TEST METHOD | SPECIFICATION | TYPICAL VALUES |
|------|-----------------------|--------------------|-------------|----------------|----------------|
| 1 | APPEARANCE | - | VISUAL | BRIGHT & CLEAR | BRIGHT & CLEAR |
| 2 | SP. GRAVITY @ 29.5 °C | g/ml | ASTD D1298 | 0.810 , Max | 0.784 |
| 3 | COLOR, Saybolt | | ASTM D 156 | 30 Max | 30 |
| 4 | FLASH POINT | deg C | ASTM D 93 | Min 75 | 80 |
| 5 | IBP | deg C | ASTM D 86 | 185 Min. | 212 |
| 6 | DRY POINT | deg C | ASTM D 86 | 275 Max | 254 |
| 7 | KIN.VISCOSITY @ 40 °C | mm ² /s | ASTM D 445 | 1.5 - 2.2 | 1.62 |
| 8 | POUR POINT | deg C | ASTM D 97 | -30 Max | -42 |
| 9 | AROMATIC CONTENT | PPM | IS 13155 | <0.1 | 0.01 |

DISCLAIMER

(1) The information given here is considered to be correct is offered for your consideration investigation & verification .
(2) No warranties are expressed or implied since the use of products are beyond our control.

Tested By

Approved by.

Q C Chemist

Manager QC

FM/QC/002,0.00;0723



SIDHE PETROCHEMICALS PRIVATE LIMITED

R.S. No. 445,446/1,446/2,448,449, Village Bhimasar,
Taluka Anjar, District Kutch, 370240, Gujarat.

CERTIFICATE OF ANALYSIS

REPORT NO. SPPL/BM/PB/0063

Date 29.04.2025

PRODUCT NAME KL 80 DA
QUANTITY 08 X 500 ML
REF.NO: 0063/2025
CUSTOMER. M/S. KLJ RESOURCESS LTD
PLACE CHENNAI

| S.NO | CHARACTERISTICS | UNIT | TEST METHOD | SPECIFICATION | TYPICAL VALUES |
|------|-----------------------|-------|-------------|----------------|----------------|
| 1 | APPEARANCE | - | VISUAL | BRIGHT & CLEAR | BRIGHT & CLEAR |
| 2 | SP. GRAVITY @ 29.5 °C | g/ml | ASTD D1298 | 0.810 , Max | 0.790 |
| 3 | COLOR, Saybolt | | ASTM D 156 | 30 Max | 30 |
| 4 | FLASH POINT | deg C | ASTM D 93 | Min 75 | 82 |
| 5 | IBP | deg C | ASTM D 86 | 185 Min. | 212 |

| | | | | | |
|----|-----------------------|--------------------|-------------|-----------|------|
| 6 | DRY POINT | deg C | ASTM D 86 | 275 Max | 256 |
| 7 | KIN.VISCOSITY @ 40 °C | mm ² /s | ASTM D 445 | 1.5 - 2.2 | 1.70 |
| 8 | POUR POINT | deg C | ASTM D 97 | -30 Max | -42 |
| 9 | AROMATIC CONTENT | PPM | IS 13155 | <0.1 | 0.01 |
| 10 | SULPHUR CONTENT | PPM | ASTM D 5453 | <10 | <10 |

DISCLAIMER

(1) The information given here is considered to be correct is offered for your consideration investigation & verification .
(2) No warranties are expressed or implied since the use of products are beyond our control.

Tested By

Approved by.

Q C Chemist

Manager QC

FM/QC/002,0.00;0723



SIDHE PETROCHEMICALS PRIVATE LIMITED

R.S. No. 445,446/1,446/2,448,449, Village Bhimasar,
Taluka Anjar, District Kutch, 370240, Gujarat.

CERTIFICATE OF ANALYSIS

REPORT NO. **SPPL/BM/PB/0068**

Date **01.05.2025**

PRODUCT NAME **SH 80 DA**
QUATITY **02 X 500 ML**
REF.NO: **0068/2025**
CUSTOMER. **M/S. PETROMIX**
PLACE **DELHI**

| S.NO | CHARACTERISTICS | UNIT | TEST METHOD | SPECIFICATION | TYPICAL VALUES |
|------|-----------------------|--------------------|-------------|----------------|----------------|
| 1 | APPEARANCE | - | VISUAL | BRIGHT & CLEAR | BRIGHT & CLEAR |
| 2 | SP. GRAVITY @ 29.5 °C | g/ml | ASTD D1298 | 0.810 , Max | 0.790 |
| 3 | COLOR, Saybolt | | ASTM D 156 | 30 Max | 30 |
| 4 | FLASH POINT | deg C | ASTM D 93 | Min 75 | 82 |
| 5 | IBP | deg C | ASTM D 86 | 185 Min. | 212 |
| 6 | DRY POINT | deg C | ASTM D 86 | 275 Max | 256 |
| 7 | KIN.VISCOSITY @ 40 °C | mm ² /s | ASTM D 445 | 1.5 - 2.2 | 1.70 |
| 8 | POUR POINT | deg C | ASTM D 97 | -30 Max | -42 |
| 9 | AROMATIC CONTENT | PPM | IS 13155 | <0.1 | 0.01 |
| 10 | SULPHUR CONTENT | PPM | ASTM D 5453 | <10 | <10 |

DISCLAIMER

(1) The information given here is considered to be correct is offered for your consideration investigation & verification .
(2) No warranties are expressed or implied since the use of products are beyond our control.

Tested By

Approved by.

Q C Chemist

Manager QC

FM/QC/002,0.00;0723



SIDHE PETROCHEMICALS PRIVATE LIMITED

R.S. No. 445,446/1,446/2,448,449, Village Bhimasar,
Taluka Anjar, District Kutch, 370240, Gujarat.

CERTIFICATE OF ANALYSIS

REPORT NO. SPPL/BM/PB/0114

Date 14.05.2025

PRODUCT NAME KL 80 DA
QUANTITY 08 X 500 ML
REF.NO: 114/2025
CUSTOMER. M/S. KLJ RESOURCES LTD
PLACE CHENNAI

| S.NO | CHARACTERISTICS | UNIT | TEST METHOD | SPECIFICATION | TYPICAL VALUES |
|------|-----------------------|--------------------|-------------|----------------|----------------|
| 1 | APPEARANCE | - | VISUAL | BRIGHT & CLEAR | BRIGHT & CLEAR |
| 2 | SP. GRAVITY @ 29.5 °C | g/ml | ASTD D1298 | 0.810 , Max | 0.790 |
| 3 | COLOR, Saybolt | | ASTM D 156 | 30 Max | 30 |
| 4 | FLASH POINT | deg C | ASTM D 93 | Min 75 | 82 |
| 5 | IBP | deg C | ASTM D 86 | 185 Min. | 212 |
| 6 | DRY POINT | deg C | ASTM D 86 | 275 Max | 256 |
| 7 | KIN.VISCOSITY @ 40 °C | mm ² /s | ASTM D 445 | 1.5 - 2.2 | 1.70 |
| 8 | POUR POINT | deg C | ASTM D 97 | -30 Max | -42 |
| 9 | AROMATIC CONTENT | PPM | IS 13155 | <0.1 | 0.01 |
| 10 | SULPHUR CONTENT | PPM | ASTM D 5453 | <10 | <10 |

DISCLAIMER

(1) The information given here is considered to be correct is offered for your consideration investigation & verification .
(2) No warranties are expressed or implied since the use of products are beyond our control.

Tested By

Approved by.

QC Chemist

Manager QC

FM/QC/002,0.00;0723



SIDHE PETROCHEMICALS PRIVATE LIMITED

R.S. No. 445,446/1,446/2,448,449, Village Bhimasar,
Taluka Anjar, District Kutch, 370240, Gujarat.

CERTIFICATE OF ANALYSIS

REPORT NO. SPPL/BM/PB/0153

DATE: 07.06.2025

PRODUCT NAME KL 80 DA
QUANTITY 01 X 01 LTR
REF NO 153/2025
CUSTOMER NAME M/S. TRANSIA PETROCHEM PVT LTD
PLACE MAHARASTA

| S.NO | CHARACTERISTICS | UNIT | TEST METHOD | SPECIFICATION | TYPICAL VALUES |
|------|-----------------------|--------------------|-------------|----------------|----------------|
| 1 | APPEARANCE@ 20°C | - | VISUAL | BRIGHT & CLEAR | BRIGHT & CLEAR |
| 2 | SP. GRAVITY @ 29.5 °C | g/ml | ASTD D1298 | 0.810 , Max | 0.790 |
| 3 | COLOR, Saybolt | | ASTM D 156 | 30 Max | 30 |
| 4 | FLASH POINT | deg C | ASTM D 93 | Min 75 | 87 |
| 5 | IBP | deg C | ASTM D 86 | 200 Min. | 212 |
| 6 | DRY POINT | deg C | ASTM D 86 | 260 Max | 256 |
| 7 | KIN.VISCOSITY @ 40 °C | mm ² /s | ASTM D 445 | 1.5, Min | 1.70 |
| 8 | POUR POINT | deg C | ASTM D 97 | <-30 | -42 |
| 9 | AROMATIC CONTENT | PPM | IS 13155 | <0.1 | 0.01 |
| 10 | SULPHUR CONTENT | PPM | ASTM D 5453 | <10 | <10 |

DISCLAIMER

(1) The information given here is considered to be correct is offered for your consideration investigation & verification .

(2) No warranties are expressed or implied since the use of products are beyoud our control.

Tested By Approved by

Q C Chemist Manager QC
FM/QC/002,0.00;0723

|  | SIDHE PETROCHEMICALS PRIVATE LIMITED R.S. No. 445,446/1,446/2,448,449, Village Bhimasar, Taluka Anjar, District Kutch, 370240, Gujarat. | | | | |
|---|--|--------------------|-------------|----------------|------------------|
| CERTIFICATE OF ANALYSIS | | | | | |
| REPORT NO. | SPPL/BM/PB/0185 | | | | DATE: 17.06.2025 |
| PRODUCT NAME | KL 80 DA | | | | |
| QUATITY | 01 X 01 LTR | | | | |
| REF NO | 185/2025 | | | | |
| CUSTOMER NAME | M/S. GOLDSTAB ORGANICS PVT LTD | | | | |
| PLACE | BHILAD | | | | |
| S.NO | CHARACTERISTICS | UNIT | TEST METHOD | SPECIFICATION | TYPICAL VALUES |
| 1 | APPEARANCE@ 20°C | - | VISUAL | BRIGHT & CLEAR | BRIGHT & CLEAR |
| 2 | SP. GRAVITY @ 29.5 °C | g/ml | ASTD D1298 | 0.810 , Max | 0.790 |
| 3 | COLOR, Saybolt | | ASTM D 156 | 30 Max | 30 |
| 4 | FLASH POINT | deg C | ASTM D 93 | Min 75 | 86 |
| 5 | IBP | deg C | ASTM D 86 | 200 Min. | 212 |
| 6 | DRY POINT | deg C | ASTM D 86 | 260 Max | 254 |
| 7 | KIN.VISCOSITY @ 40 °C | mm ² /s | ASTM D 445 | 1.5, Min | 1.71 |
| 8 | POUR POINT | deg C | ASTM D 97 | <-30 | -42 |
| 9 | AROMATIC CONTENT | PPM | IS 13155 | <0.1 | 0.01 |
| 10 | SULPHUR CONTENT | PPM | ASTM D 5453 | <10 | <10 |

DISCLAIMER

(1) The information given here is considered to be correct is offered for your consideration investigation & verification .

(2) No warranties are expressed or implied since the use of products are beyoud our control.

Tested By

Q C Chemist

Approved by

Manager QC

FM/QC/002,0.00;0723