



SIDHE PETROCHEMICALS PRIVATE LIMITED

R.S. No. 445,446/1,446/2,448,449,
Village Bhimasar, Taluka Anjar, District Kutch, 370240, Gujarat.

CERTIFICATE OF ANALYSIS

PRODUCT NAME SH 65 PF

S.NO	CHARACTERISTICS	UNIT	TEST METHOD	SPECIFICATION	TYPICAL VALUES
1	APPEARANCE	-	VISUAL	BRIGHT & CLEAR	BRIGHT & CLEAR
2	DENSITY @ 29.5 °C	g/ml	ASTD D1298	0.745, typ	0.738
3	COLOR, Saybolt		ASTM D 156	30 Max	30
4	FLASH POINT	deg C	ASTM D 93	Min 65	72
5	IBP	deg C	ASTM D 86	180 Min.	184
6	FBP	deg C	ASTM D 86	250 Max	244
7	KIN.VISCOSITY @ 40 °C	mm ² /s	ASTM D 445	1.50 Max	1.39
8	POUR POINT	deg C	ASTM D 97	≤15	-21

DISCLAIMER

- (1) The information given here is considered to be correct is offered for your consideration investigation & verification .
(2) No warranties are expressed or implied since the use of products are beyond our control.

Tested By

Approved by

Q C Chemist

Manager QC

FM/QC/002,0.00;0723