

# Sidwak

## LIQUID WAX

### Grades



### Description:

Liquid wax is a type of wax, typically used for polishing and protecting surfaces, that has a liquid consistency at room temperature

### Applications:

1. Car Detailing
2. Floor Polishing
3. Candle Making

### Industrial Use:

1. Plastics Industry:
2. Semiconductor Industry
3. Agriculture
4. Waterproofing



Property	Method	SPECIFICATIONS			
		SH 120 LA	SH 370	SH 300	SH 240
Appearance@20°C	Visual	Bright & Clear	Bright & Clear	Waxy Like(Bright & Clear)	-
Density @29.5°C/ 50°C	ASTD D1298	0.790	0.775	0.772	-
Colour Saybolt	ASTM D 156	+30	WHITE	+30	1
Flash Point (°C)	ASTM D 93	180	180-200	-	240
Pour Point °C	ASTM D 97	+24	+35	34	
Oil Content	ASTM D-721	-	-	-	3.4 (MAX 5)
Melting Point (°C)	SPPL/QA-SOP/005	35.6	30-35	30-35	65
Kin Viscosity @40°C (mm <sup>2</sup> /s)	ASTM D 445	5.63	3.15	-	-
IBP (°F)	ASTM D 86	332	-	-	-
FBP (°F)	ASTM D 86	368	-	-	-
Penetration At 77°F	ASTM D-5	150	-	-	43
Packing	-	Drum/Bulk	Drum	Drum	Drum
Uses	-	Speciality Chemical, Viscosity Modifier	Industrial Use, Viscosity Modifier		